

TRT'S CRANE OUTRIGGER PADS PROVIDE MAXIMUM STRENGTH (FOR SIZE) WHILE MINIMISING TARE WEIGHT.

EASY TO TRANSPORT AND SET UP, THEY IMPROVE OVERALL JOB EFFICIENCY AND SITE SAFETY.

Engineering Data

Ensure your crane is supported safely for all ground conditions. TRT makes this simple. The standard size crane pads, in the table overleaf, come with engineering drawings and ground pressure data, making site and lift planning easy.

Fast and Easy set-up

TRT's high quality steel Crane Outrigger Pads are easily deployed on any job site. They are being used on construction and lift sites throughout Australia and New Zealand. transporting, lifting and moving is no problem. TRT Crane Pads come with trunnions as a standard lifting and transport attachment unless otherwise specified.

Robust Construction

Manufactured for maximum strength using Hardox™ high tensile steel and a honeycomb construction, they have unparalleled quality and performance when compared to other options. TRT's unique pad design helps to minimise deflection and protect underground services from damage. They are able to span trenches and manhole covers without compromising ground stability.

Safety First


The non-slip surface and angled sides are designed to make the pads safer on a job site. The angled sides are designed to prevent tyre damage to other vehicles, especially in smaller work areas.





CRANE PAD SIZE CHART

TRT's Crane Outrigger Pads are available in a variety of standard sizes to suit most applications and are supplied in a set of 4 pads.



Pad (set of 4)	Length (m)	Width (m)	Height (m)	Surface (m²)	Weight (kg)	Attachments
PAD-014	1.20	1.20	0.19	1.44	257	Forklift Pockets & D-Rings
PAD-030	2.37	1.27	0.19	3.01	480	Trunnions
PAD-031	2.10	1.48	0.19	3.10	470	Trunnions
PAD-035	2.37	1.48	0.19	3.50	675	Trunnions
PAD-039	2.37	1.63	0.19	3.86	771	Trunnions
PAD-050	2.47	2.03	0.19	5.00	1161	Trunnions
PAD-061	2.98	2.04	0.19	6.08	1409	Trunnions
PAD-082	3.40	2.40	0.25	8.16	2121	Trunnions
PAD-105L	4.38	2.40	0.25	10.5	3065	Trunnions & Twist Lock Corners*
PAD-143*	5.97	2.40	0.25	14.33	4127	Trunnions & Twist Lock Corners*

TRANSPORT ATTACHMENT **OPTIONS FOR CRANE PADS**

TRT Crane Pads come with trunnions as a standard lifting and transport attachment unless otherwise specified on the size chart. Prices may vary depending on the transport attachments required.

*PAD-143 has the footprint of a 20ft container with the twist lock corners to fit any standard container carrier for transport.



The faster and more safely your crane and ancillary equipment can get to site and set up, the more efficient and cost effective your job.

TRT manufactured Crane Support Trailers are designed fit for purpose, using the latest transport technology. We know cranes and we know how to get them from A to B safely and productively.

Ask about new Versalock for easy reconfiguration to carry components for any crane.

OUR RANGE:

SEMI TRAILER B TRAINS COUNTER WEIGHT TRAILERS CRANE EQUIPMENT TRAILERS LOW LOADERS PLATFORM TRAILERS











TRT (2021) Pty Ltd

1028 Lytton Road, Murarrie, QLD 4172 Phone: +61 7 3890 8800 Email: cranesales@trtaust.com.au www.trtaustralia.com.au

48 Maui Street, Pukete Industrial Estate P.O Box 10076, Te Rapa, Hamilton 3241 Phone: +64 7 849 4839

Email: cranesales@trt.co.nz www.trt.co.nz