



TRT Crane Pads evenly distribute outrigger crane loads. Quality engineering ensures all TRT Crane Pads adhere to the CICA industry standards.

PAD-050-T

PAD WEIGHT: 1186kg

MINIMUM FOOT SIZE: Ø300mm

MAXIMUM SPAN: 1000mm

MAXIMUM LOAD: 200T

Ground Pressure Rating

WIDTH (mm)		2470
LENGTH (mm)		2025
CONTACT AREA (m ²)		5.0
GROUND PRESSURE	kg / m ²	kPa
25 TONNE	4998	49
50 TONNE	9997	98
100 TONNE	19993	196
150 TONNE	29990	294
200 TONNE	39986	392

UNLESS OTHERWISE STATED

GENERAL TOLERANCES	0.00 = ±0.05 0.0 = ±0.2 0 = ±0.5	THIRD ANGLE PROJECTION
ANGLES	0 = ±0.5°	SURFACE FINISH (µm)

WELDING: ALL INFORMATION SHALL COMPLY WITH NZ/AS 1554:2000 PT 1 CATEGORY SP UNLESS OTHERWISE STATED AND SHALL BE WELDED TO A QUALIFIED PROCEDURE, BY A WELDER QUALIFIED FOR THE APPROPRIATE POSITION AND SUPERVISED BY A WELDING SUPERVISOR. WIRE BUFF ALL STEEL COMPONENTS PRIOR TO WELDING

THIS DRAWING IS © COPYRIGHT AND IS THE PROPERTY OF TIDD ROSS TODD LTD. IT IS FURNISHED TO YOU FOR CONFIDENTIAL INFORMATION PURPOSES ONLY AND IS NOT TO BE DISCLOSED TO ANYONE ELSE OR USED FOR MANUFACTURING PURPOSES WITHOUT THE EXPRESS WRITTEN PERMISSION OF TIDD ROSS TODD LTD.

REV	DATE	COMMENT	NAME



48 Maui Street
Hamilton
New Zealand
Ph: +64 7 849 4839
Email: trt@trt.co.nz
ISO 9001:2015

NAME	DATE	TITLE:	CRANE PAD 2470 X 2025 ASSY
DRAWN	JH	29/05/20	
CHK'D	-	-	SHEET 3 OF 3
APPV'D	-	-	
DO NOT SCALE DRAWINGS IN mm's	STATUS - M	SCALE:1:20	DWG NO. PAD-050
			REVISION A