

## 3 Axle Equipment Semi Trailer

Drawing reference: 268-A04 W REV A

<b>Forward Length</b>	6.52m
<b>Deck Length</b>	10.1m
<b>Width</b>	2.5m
<b>GVM Rating</b>	40 tonne
<b>Tare Weight</b>	5,100kg approx.
<b>Axle Spacing</b>	1.25m
<b>King Pin</b>	2" bolt in
<b>Skid Plate Height</b>	1260mm TBC
<b>Chassis</b>	Fabricated I Beam construction from Grade 80 high tensile steel. Special load restraint mechanism built in for Crane components
<b>Coaming Rail</b>	Profiled Flat bar with pressed edge c/w rope rail.
<b>Load Restraints</b>	Rope rails on coaming rail. Tie down points for Slings.
<b>Decking</b>	3mm Plate with Non-skid coating for safety
<b>Suspension</b>	Heavy-duty BPW air suspension.
<b>Mounting brackets</b>	Specially designed mounting plates are located on the trailer for specific product to be loaded in the right location so that the trailer weighs out legally. Mounts are designed for safe easy load/unload and securing of load.
<b>Deck access</b>	Steps at rear bumper provide access to the deck.
<b>Safety</b>	Handrail system fitted, non-skid surface to prevent slippage and special mounting brackets for ease of load/unload
<b>Axles</b>	3 of 19.5 BPW disc braked axles - 10 stud axles with grease filled Hub.
<b>Rims</b>	12 of 19.5 - 10 stud Polished Alloy wheels.
<b>Tyres</b>	12 of 265 70R 19.5 tubeless radials.
<b>Spare Tyre Mount</b>	No spare or mount supplied to meet tare weight

<b>Braking</b>	To meet ADR regulations, EBS
<b>Lighting</b>	LED lighting system to meet ADR requirements.
<b>Yard Release</b>	Fitted on RHS.
<b>Landing Legs</b>	Just wind up legs
<b>Paint</b>	Grit blasted, primed and painted in 2K paint system, electrostatically applied for full coverage.

*Please Note: Specifications shown above for Australia, please contact us for specification for New Zealand and other countries.*

## Trailer Options

TRT has a wide range of standard and customisable options available for each trailer. These options are designed fit for purpose.

## Design and Engineering

TRT has a full range of design and build capability. If you require a transport solution or have a specific purpose for your new trailer, TRT are able to work with you from initial sketches or specifications to create fully engineered design solutions for your payloads now and in the future.

## Manufacturing

TRT design, fabricate and manufacture in house. TRT are accredited ISO 9001:2015, quality is critical to ensure your trailer will meet and in most cases exceed your requirements to minimise payback period. When you choose a trailer from TRT, it's for the long haul.



### NEW ZEALAND

PHONE: +64 7 849 4839  
 ADDRESS: 48 Maui St, Hamilton  
 EMAIL: trailers@trt.co.nz  
 WEB: www.trt.co.nz

### AUSTRALIA

PHONE: 1800 802 912  
 ADDRESS: 1028 Lytton Rd, Murarrie, QLD 4172  
 EMAIL: trailers@trtaust.com.au  
 WEB: www.trtaust.com.au